



MERCURY PLASTICS, INC.

Phone: 440.632.5281

Fax: 440.632.5606

Installation Instructions for Merflex[®] PEX OT Refrigerator Water Supply Lines

IMPORTANT NOTE: Manufacturer assumes no responsibility for failure due to improper installation.

- Turn off water supply.
- Make sure the water supply stop is oriented at a forty-five degree angle to the installed wall and not perpendicular to the refrigerator.
- Hand-tighten connection(s), then tighten with a wrench two and one half (2-1/2) additional turns.
- Turn on water.
- If a leak appears, tighten up to one additional turn. If the leak persists, discard the line and replace.
- DO NOT OVERTIGHTEN as this can lead to short and long-term failure.
- When moving the refrigerator back into place, make sure the end connections and tubing are not side-loaded, kinked, crimped, or bent into a radius smaller than 3" as this may cause failure.

CAUTION: This PEX water supply line is recommended for one-time installation and use. DO NOT REUSE OR RECONNECT. Replace every five years. All fittings and end connectors should be free of pipe dope, compounds, sealant and thread tape. Do not install or store in direct sunlight as failure may occur.

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

LIMITATION OF REMEDY AND DISCLAIMER OF WARRANTIES: Manufacturer warrants this product to be free of manufacturing defects. The sole and exclusive remedy for any product proven defective is limited to replacement of the defective product or the refund of the purchase price paid. No other warranty or guarantee of any kind is made by Manufacturer, expressed or implied, statutory, by operation of law or otherwise. ALL IMPLIED WARRANTIES INCLUDING THOSE FOR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.